8H型自動封罐機 Automatic 8-H Double Seamer

S-B49 8H自動封罐機適用於圓空罐或食品罐之捲封。反邊(或充填)好之罐身由分罐螺桿及鏈條帶入捲封站,罐蓋由一組分割刀分割並由推爪送進,捲封站具八組捲封軸,旋轉之托罐盤將罐身托起與罐蓋結合,再由二只捲輪執行捲封工作。機械凸輪脫罐桿將捲封好之罐身打下,捲封後之罐身由轉盤帶出。捲封品質符合國際標準。構造簡單及多重安全設計,操作及保養容易。

S-B49

S-B49 Automatic 8H Seamer is specially designed for round empty or food can closing. Flanged (or filled) can is fed forward through a timing screw and a chain to enter seaming station equipped with 8 sets of seaming spindle. End is separated by a separator and fed forward by a pusher. Spin lifter plate lift can up to meet with end. Two seaming rollers undertake seaming operation. Cam driven knock out pad release the seamed can from chuck and seamed can is carried out by a turret. Seam quality meet international standard. Simple structure and multiple safety devices, easy for operation and maintenance.

Certified by

ISO-9001

Quality Assurance System





新益機械工廠股份有限公司 SHIN I MACHINERY WORKS CO., LTD.

8 H型自動封罐機

Automatic 8-H Double Seamer


特點:

- ●無罐無蓋裝置之度(NCNC)及罐蓋不足自動停機裝置。
- ●使用人機介面(觸控螢幕)控制系統及變頻器作設定及無段變速控制。
- 多處安全停機裝置.確保機台壽命及捲封品質。
- ●與罐身接觸面均鍍絡處理或不銹鋼材質,減少擦傷。
- ●自動機油潤滑中心軸傳動機構及托罐座。
- ●換型容易,保養容易。

Feature:

- No can No cover system and low cover stacking detecting.
- Ues human-machine interface (touchable screen) control system and inverter for set up and variable speed control.
- Operational safety controls are built for long life.
- Can guide and turret with chromium plating or stainless steel material.
- Central shaft driving system and lifter plate set are lubricated by oil provided by an auto pump.
- Easy for different can size changeover.





規格 SPECIFICATIONS:

| 機 型 MA | ACHINE TPYE | S-B49 |
|-------------|--------------------------|--------------------------------------|
| 適用罐徑Ra | ange of Can Dia. | 202~401 D |
| 適用罐高Ra | ange of Can Height | 42~180 mm |
| 每分鐘產能 Ca | apacity per minute | Up to 720 CPM, depending on can size |
| 需要馬力Ho | orse Power Required | 10 HP |
| 安裝面積及高度 Flo | por Spcae Overall Height | 2980Lx1260Wx2180H mm |
| 淨 重 Ne | et Weight(approx) | 3500 kgs |

※規格如有變更,恕不另通知 Subject to change without notice.

新益機械工廠股份有限公司 SHIN-I MACHINERY WORKS CO., LTD.

台灣省台中縣清水鎮清水里中正街43號 NO.43 CHUNG-CHENG STREET, CHING SHUI, TAICHUNG, TAIWAN. TEL:886-(04)2623-8181 FAX:886-(04)2623-2129

Web address: http://www.shinican.com
E-mail: shinican@ms15.hinet.net

| \$277 444 | 12.00 |
|-----------|--------|
| 經錐 | 1121 . |
| AGE | |
| MUL | 141 . |